

Fairmount Walk-in-Tub

OHS-5129 Inward Swinging Door



GENERAL SPECIFICATION

Dimensions 51 ¼" L x 29 ¾" W x 37 ½" H

Weight 210lbs

Operating Capacity55-60 gallons

FEATURES

PVC DRAIN

- Size 2"
- Horizontal
- Plunger with Chain

DOOR

- Opening Width 18 ½"
- Patented Door System Technology
- Aluminum Door and Frame

Acrylic Shell

- White
- Acrylic
- Non-skid Floor
- ADA Height Seat
- Acrylic Surface with Fiberglass Substrate
- Two Grab Bars
- Stainless Steel Frame
- Front and Corner Deck for Faucet Locations

High Flow Faucets

- 14 GPM Flow Rate
- ¾" feed lines
- IPT Thread connections
- Shower Wand

OPTIONS

- Left or Right-Hand Drain
- Air jet System
- Water jet System
- Ozonator
- Pure Bubbles
- Aromatherapy
- Chromatherapy
- Heated Seat Back

Compliance Certification – Meets or Exceeds the Following Specifications:

- cETL – Intertek
- cUPC / USPC – IAPMO
- ANSI Z 124.1.2 – for Plastic Bathtubs
- ASME A112.19.7 – Whirlpool Appliances
- ASME A112.19.15 – for Walk in Bathtubs
- CSA B45.5 – Canadian Plumbing Fixtures

Before ordering or installing consider future access to essential components

To continually improve our product, specifications and equipment. Configurations are subject to change without notice.

1-877-826-6666

www.safetybathtubs.com

Fairmount Walk-in Tub

